

A.S.S.

Anti-Seize Spray



A.S.S. ANTI SEIZE SPRAY is a thick spray lubricant and coating to use wherever metal contacts metal. Ensures quick and easy disconnection of bolts, spark plugs, threaded fittings, bushings and more while preventing galling, seizing and thread distortion. This heat resistant coating acts as a barrier to withstand extreme heat (to 2000°F), pressure and friction. It shortens downtime, reduces costly replacements of parts, stops corrosion, is non-melting, waterproof and highly resistant to chemicals, solvents and gases (except oxygen). Will not wash off, melt, or harden. **A.S.S. ANTI SEIZE SPRAY** contains synthetic oil, extremely fine aluminum and graphite particles and is recommended for use in temperature ranges from -35°F to 750°F. does not contain any chlorinated or fluorinated solvents.

Directions: Shake can well before using. Make sure area is free of grease and dirt by cleaning with Omega's **POW** heavy duty degreaser. Apply product to form a solid film over surface. Assemble and wipe off excess with degreaser.

Areas of Use:

- *nuts & bolts
- *threaded fittings
- *bushings
- *bearings
- *rollers
- *conveyors
- *spark plugs
- *hand and motor operated valves
- *vehicle repair garages
- *municipalities
- *ship yards
- *machine shops
- *industrial plants

Health	1
Flammability	3
Reactivity	1
Protection	G

Appearance and odor.....	Silver gray grease, Ether-like odor
Specific Gravity.....	Concetrate - 0.91
Propellant.....	Propane/N-Butane
VOC.....	41.36%
NFPA Fire Rating.....	Extremely Flammable

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134