

C & G

Caulking and gasket maker



C & G is a R.T.V. Silicone caulk and sealant that is ideal for use wherever a strong weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Bonds nameplates, machinery flanges, glass, signs, windows, doors and more. **C & G** features excellent adhesion and high chemical resistance. Useful for sealing cracks in plumbing fixtures, low pressure water and drain lines, ventilating duct work, plumbing fixtures and electrical connections. Remains flexible at temperatures from -85° to +500° F and will not sag or shrink eliminating the need to reseal areas due to shrinkage. When resealing an area where another brand of caulk has been used, use Omega's **JELL STRIP** to remove old caulk easily.

Available in Clear, White, Red, Black or Blue.

Directions: For best adhesion, make sure area is free of oil, tar, dirt and dust by cleaning with Omega's **MEGA POWER** or **POW**. Hold can at 45 degree angle and apply a continuous bead to the surface, encircling any bolt holes. For adhesion to both parts assemble immediately. For adhesion to one part allow to sit for 10-15 minutes. Full cure in 24 hours. Do not use on cylinder heads, intake and exhaust manifolds, carburetors, or parts continuously immersed in gasoline.

Areas of Use:

- *caulk tubs, sinks, showers
- *seals around doors, windows, walls
- *weather stripping
- *bonds carpet and upholstery
- *seal windshields, exterior lights
- *Forms in place gaskets and seals for pumps, oil and transmission pans, gear boxes, compressors, machine covers, housings, and more

Health	1
Flammability	1
Reactivity	0
Protection	B

Appearance and odor.....	Various colors, Acetic odor
Specific Gravity.....	Concentrate - 1.03
Propellant.....	Pressurized Aerosol
VOC.....	N/A
NFPA Fire Rating.....	N/A

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134