

C-Patch

Concrete Filler and Sealant



C PATCH is a durable sealant specifically formulated to repair cracks and holes in concrete, mortar and masonry. C PATCH contains silicone additives for improved adhesion and water resistance.C PATCH forms a durable, flexible and water-tight seal. C PATCHresists gas, oil, grease and salt. Interior/exterior use. Paintable. ADHERES TO: Concrete, mortar, cinder block, stucco, brick, wood, and stone.

FOR BEST RESULTS: Clean area with Omega's MEGA POWER degreaser to remove any grease or oily residue for best adhesion. Do not apply when temperatures are below 40°F, or when rain or freezing temperatures are eminent. Store away from extreme hot and cold temperatures . Not recommended for under water applications. Joint size should not exceed 1/2" wide by 1/2" deep. Allow to cure 24 hours before direct exposure to water. Serviceable for pedestrian and vehicular traffic after 24 hours (minimum). C PATCH fully cures in 7-14 days, depending on temperature, humidity and depth of fill.

DIRECTIONS: Remove loose dirt and debris. Apply **C PATCH** to a clean, dry surface. Cut nozzle at a 45° angle to desired bead size. Load cartridge in caulking gun. Fill crack or gap with **C PATCH**. Smooth bead if necessary. Clean up excess uncured **C PATCH** with damp sponge or cloth. Paintable after 2 hours (longer in cool or humid conditions) with latex or oil-based paints. **COVERAGE:** 56 linear feet at 3/16" diameter bead.

WARNING! Phthalate Esters, Petroleum Disillates and Ethylene Glycol.

Health	1
Flammability	1
Reactivity	0
Protection	Δ

Areas of Use:

- *apartment complexes
- *utility companies
- *cities and counties
- *amusement parks
- *industrial facilities
- *plumbing departments
- *grounds maintenance
- *warehouses

Appearance and odorColored paste, ammonia odor		
Specific GravityConcentrate - 1.5196		
VOC	5%	
NEPA Fire Rating	Non-flammable	

ONLY OMEGATM

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com/onlyomega Fax: 707-864-8134