

# C-Patch

Concrete filler and sealant



**C PATCH** is a highly adhesive concrete and mortar filler and sealer that is designed to repair cracks and holes in concrete, masonry and mortar. It remains flexible so it will not crack and chip out of the area repaired. Provides a water tight seal and is resistant to oil, grease, gasoline, and salt water. **C PATCH** is tack free and paintable after 30 minutes. Final cure in 24 hours. **C PATCH** will adhere to concrete, cinder block, mortar, brick, and stone and is ideal for sealing and patching driveways, sidewalks, warehouse floors and other concrete surfaces.

**Directions:** Remove loose dirt and debris. Trim nozzle to desired bead size, and load into caulking gun. Fill cracks and holes with sealant and clean up immediately with a damp cloth.

**FOR BEST RESULTS:** Clean area with Omega's **MEGA POWER** degreaser to remove any grease or oily residue for best adhesion. Do not apply when temperatures are below 40°, or when rain or freezing temperatures are eminent. Store away from extreme temperatures. Not recommended for under water applications. Joint size should not exceed 1/2". Allow to fully cure for 24 hours before exposure to water. **CAUTION:** Contains Ethylene Glycol

**Areas of Use:**

- \*apartment complexes
- \*utility companies
- \*cities and counties
- \*amusement parks
- \*industrial facilities
- \*plumbing departments
- \*grounds maintenance
- \*warehouses

Health	1
Flammability	1
Reactivity	0
Protection	A

Appearance and odor.....	Colored paste, ammonia odor
Specific Gravity.....	Concentrate - 1.5196
VOC.....	5%
NFPA Fire Rating.....	Non-flammable

**ONLY OMEGA™**

Fairfield, CA 94534

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134