

# Coat It

High Solids Industrial Coating



**COAT IT** can be used interior/exterior single coat hiding power. **COAT IT** dries quickly protects against rust, weather, oil, gasoline, abrasion and most corrosive chemicals and making **COAT IT** the best choice for any job. Can be used on wood and metal, home, automotive, industrial, marine, and construction. Resists fading, cracking, chipping and peeling. Does not contain lead, CFC's chromates or chlorinated solvents. **Available in White, Black, Red, Yellow and Blue.**

**DIRECTIONS:** 1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can temperature is between 40°F and 90°F (4°C and 32°C). 2. Shake can at least one minute after rattle is heard and occasionally during use. 3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat. Recoat — For best results recoat within 1 hour or after 48 hours. This time varies with curing temperature, humidity, and film thickness. Test a small hidden area before recoating. 4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert spray-head with a gentle twisting motion. 5. To clear sprayhead for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

White

Health	2
Flammability	4
Reactivity	1
Protection	G

Blue

Health	1
Flammability	4
Reactivity	3
Protection	G

Yellow, Red

Health	1
Flammability	3
Reactivity	3
Protection	G

Black

Health	1
Flammability	4
Reactivity	3
Protection	X

**Areas of Use:**

- \*Utility covers
- \*Wood
- \*Masonry
- \*Paint shops
- \*Metal
- \*Plastic
- \*Building maintenance
- \*Municipalities

Appearance and odor.....	various colored liquid, solvent odor
Specific Gravity.....	Concentrate - 0.77-0.90
Propellant.....	Mixture
VOC.....	46-48%
NFPA Fire Rating.....	Extremely-flammable Spray

**ONLY OMEGA™**

Fairfield, CA 94534

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) [www.facebook.com/onlyomega](http://www.facebook.com/onlyomega) Fax: 707-864-8134