

Dri Moly

Moly Based Dry Lubricant



DRI MOLY is a molybdenum disulfide dry film lubricant that withstands high pressures and temperatures. Lubricates moving parts of all kinds. Fast drying with minimal transfer. Protects from rusting and corrosion by displacing moisture. Reduces metal to metal contact on treated surfaces. Service temperatures range from -40°F to 600°F. Convenient aerosol is ideal for lubricating surfaces where a liquid lubricant is not practical. **DRI MOLY** quick drying, non-tacky finish adheres well to all metals, most plastics, glass and rubber. Molybdenum disulfide replaces graphite to free frozen surfaces, stop galling and seizing of metals and prevents chattering, extending the life of machinery and equipment. Provides a protective barrier that resists dust and abrasive particles and withstands water, oils, alkali and most acids.

Directions: Shake can well before using. Clean surface thoroughly with Omega's **MEGA POWER** degreaser. Hold can 6 to 8 inches from surface and apply a thin, even film. Thick coats decrease efficiency. Allow 1 to 5 minutes for adequate drying. The concentration of solids in this product may clog nozzle. Shake vigorously and often. Before storing, turn can upside-down and spray until clear.

Areas of Use:

- *ovens and conveyors
- *rubber mold release
- *engine components
- *aircraft
- *chemical plants
- *printing
- *chain lubrication
- *machine tools
- *pump assemblies
- *turbines and compressors
- *boilers and gears
- *oil and ore drills

Health	2
Flammability	3
Reactivity	1
Protection	B

Appearance and odor.....	Charcoal Gray, solvent based aerosol, with mild sweet odor.
Specific Gravity.....	Concentrate - 1.27
Propellant.....	Hydrocarbon
Volatile by Vol.....	96%
NFPA Fire Rating.....	Extremely Flammable Spray

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com/onlyomega Fax: 707-864-8134