

# Dri Moly



Moly based dry lubricant



**MOLY-LUBE** is an extreme condition, dry, friction reducing lubricant and anti-seize coating. Contains no silicone, grease oil or graphite. The moly film has low coefficient of friction providing excellent lubricating properties without attraction of dust or dirt. Suitable for temperatures from -110° to +1050° F. Also withstands pressures up to 100,000 psi. **MOLY-LUBE** is inert to water, oil, alkalis, and many acids. Will adhere to metals, most plastics, glass and rubber. Excellent anti-seize properties were maintained with steel bolts in super heated steam installations after exposure to 1050 degrees and 20% salt solutions! Meets MIL spec MIL-A-907D, anti-seize compound High Temp.

**Directions:** Shake vigorously before each use. Clean area with Omega's **MEGA POWER** degreaser. Hold can about 8 to 10 inches from surface and saturate area to be lubricated.

**Areas of Use:**

- \*ovens and conveyors
- \*rubber mold release
- \*engine components
- \*aircraft
- \*chemical plants
- \*printing
- \*chain lubrication
- \*machine tools
- \*pump assemblies
- \*turbines and compressors
- \*boilers and gears
- \*oil and ore drills

Health	2
Flammability	1
Reactivity	1
Protection	G

Appearance and odor.....	Dark gray viscous liquid with solvent odor
Specific Gravity.....	Concentrate - 1.2
Propellant.....	Liquefied Petroleum Gas
VOC.....	36.1%
NFPA Fire Rating.....	Extremely Flammable Spray

**ONLY OMEGA™**

Fairfield, CA 94534

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134