

Ex-Pand



Expanding foam insulation
Flame retardant formula



EX-PAND is a unique one part urethane foam which expands as it dries and solidifies. Fills cracks and holes that caulk can't! Sprays as a liquid then expands and cures to a durable semi-rigid closed cell foam insulation. Each can dispenses over 250 linear feet of product when sprayed in a 3/8 inch cured bead. Forms a water resistant, weather resistant and airtight bond on masonry, wood, metal, glass, tile and most plastics. **EX-PAND** dries tack free in 15-30 minutes. Fills cracks, and plugs holes eliminating energy escape, dampens sound, and inhibits the entrance of insects or rodents. Makes a great insulating sealant around doors, windows, skylights, and A/C ventilation and heating ducts. Deadens sound when applied to sheet metal and conforms to any shape as it expands. 1" thickness yields R-5 insulating

factor. Contains flame retardant. For best results use remainder of can within 30 days of first use.

Directions: Clean grease and dirt from area with a degreasing cleaner such as Omega's **BIO POWER** or **MEGA POWER**. Shake well. Invert can and press trigger slowly. Do not fill cavity completely as product will expand 200-300%. Clean up unwanted uncured foam immediately with paint thinner or acetone. Cured foam can be cut or sanded as needed.

Areas of Use:

- *plumbing
- *HVAC trades
- *auto and truck doors
- *refrigeration units
- *building superintendents
- *hotels
- *hospitals
- *factories

Health	2
Flammability	2
Reactivity	1
Protection	B

Appearance and odor.....	Viscous liquid that foams to an off white to yellowish froth
Specific Gravity.....	Concentrate - 1.1
Propellant.....	Liquefied Petroleum Gas
VOC.....	<25%
NFPA Fire Rating.....	Flammable Spray

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134