

High-Tac A

Aerosol grease with
Teflon and tackifiers



This high tack, clear lubricating gel, provides lubrication at temperatures from -30°F to +500°F. Penetrates as oil to lubrication point, then forms into tacky grease like gel. Deposits a fine Teflon and gel lubricant mixture deep inside working parts. **HIGH-TAC A** resists water washout and weathering. Prevents rust and corrosion while covering surfaces with a moisture proof barrier film. Clean dirt and old lubricant off of surface with Omega's **POW** heavy duty degreaser.

Directions: Shake well. Spray area holding can 12-14 inches from surface. For hard to reach areas, insert tube into actuator.

Areas of Use:

- *machine shops
- *manufacturing
- *HVAC and plumbing
- *fleet vehicles
- *forklifts
- *chains
- *gears
- *cable and wire rope
- *valves
- *bearings
- *bushings

Health	2
Flammability	3
Reactivity	0
Protection	B

Appearance and odor.....	Light beige, Etheral odor
Specific Gravity.....	Concentrate - 0.724
Propellant.....	Mixture
VOC.....	N/A
NFPA Fire Rating.....	Extremely-flammable Spray

ONLY OMEGA™

Fairfield, CA 94534
1-800-571-7347 www.onlyomega.com Fax: 707-864-8134