

Jell Strip

Gel Based Paint and Varnish Stripper
Water Wash off



JELL STRIP Gel formulation paint remover quickly removes paint, epoxy paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. **JELL STRIP** has been authorized by the USDA for use in federally inspected meat and poultry plants. **JELL STRIP** is used by auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. **JELL STRIP** can be used on metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders. Coat the clean surface with Omega's **PROTECT IT** to prevent any new markings by vandals from sticking to the surface.

Directions: SHAKE WELL BEFORE USING. Holding can 8 to 10 inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow **JELL STRIP** to complete blistering before removing

Areas of Use:

- *heavy duty graffiti removal
- *decal removal
- *adhesive removal
- *wood and metal refinishing
- *departments of transportation
- *municipalities
- *sign shops
- *vehicle maintenance shops
- *plumbing departments

Health	3
Flammability	2
Reactivity	0
Protection	B

Appearance and odor.....	Viscous, hazy liquid.
Specific Gravity.....	Concentrate -1.20
Propellant.....	Propane/N-Butane
% Volatile by Wt./By Vol.....	98%
NFPA Fire Rating.....	Flammable Spray

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com/onlyomega Fax: 707-864-8134