Metal Protect

Wax like coating to protect parts from corrosion

METAL PROTECT provides a long term flexible, dirt resistant, anti-rust and anti-corrosion coating that will not crack, peel or flake. Protects metals from exposure to weather, high humidity, chemical fumes and salt spray. The flexible film is non-tacky and effective from -40° to 175° F. Excellent for protecting parts in transit or storage, and is translucent so that part numbers or identification codes underneath can be read easily. **METAL PROTECT** can be easily removed with mineral spirits or Omega's **MEGA SAFE** safety solvent when necessary. The convenient aerosol packaging is portable and easy to use. It is non-chlorinated and ozone safe. Meets Mil Spec MIL-C-16173D-Grade 4 and MIL -C-83933A.

OMEGA

SUPPLY,

ONLY OM

Directions: Clean surface with Omega's **MEGA POWER** degreaser to ensure surface is free from dirt and dust during storage. Allow to dry completely. Spray a thin uniform film. Allow approximately 5 minutes to set up. For more severe storage conditions, a second coating can be applied within a few minutes. Complete cure in approximately 2 hours.

Areas of Use:

*milled parts
*parts in transit
*parts in storage
*maintenance crews
*universities
*schools
*maintenance crews
*large molds
*seasonal equipment

Appearance and odor	
Specific Gravity	Concentrate - 0.848
Propellant	Liquefied Petroleum Gas
VOC	76.33%
NFPA Fire Rating	

Fairfield, CA 94534 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134

ONLY OMEGATM

Health1Flammability3Reactivity0ProtectionB

OMEG

NDUSTRIA

SUPPL

TAL PARTS

OTECTOR

LOWS PARTS TO BE IDENTIFIE