

O.G.L.

Open Gear Lubricant



This high tack **OPEN GEAR LUBRICANT** penetrates deep into gear teeth and cables before thickening to a heavy black stringy lubricant that bonds a Molybdenum Disulfide shield to parts, maintaining a cushion of lubricant between friction producing surfaces. Protects surfaces from corrosion and metal to metal contact, plus it automatically re-coats gear teeth with each revolution of the mechanism. **O.G.L.** contains high wear resistance additives to prevent viscosity breakdown and throw-off. Will not wash off, dry out, crack or peel. The unique dual spray valve provides either a fan spray or long range pinpoint spray to reduce disassembly time and make preventive maintenance easier. **O.G.L.** is non-chlorinated and has low VOC content. To clean up overspray or to remove old lubricant before application, use Omega's **NATURAL WAY** heavy duty degreaser.

Directions: Press valve down for fan spray, and forward for jet stream application in hard to reach areas (jet stream sprays approximately 8 feet). Apply product liberally to all surfaces to be lubricated.

Areas of Use:

- *elevators
- *drag lines
- *earthmoving equipment
- *construction trades
- *industrial machinery
- *shipyards
- *drilling rigs
- *underwater lubrication
- *trash trucks
- *street cleaning machines

Health	2
Flammability	1
Reactivity	0
Protection	G

Appearance and odor.....	Black viscous liquid, Solvent odor
Specific Gravity.....	Concentrate - 1.08
Propellant.....	Liquefied Petroleum Gas
VOC.....	72.01%
NFPA Fire Rating.....	Flammable Spray

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134