

Omega A.F.S.

Asphalt Filler & Sealer



OMEGA A.F.S. is the ultimate driveway sealer. The advanced gel formula enables the product to stay completely mixed in the container and eliminates the need for stirring. No more mess or extra work as **OMEGA A.F.S.** applies easier, cleaner and faster! Advanced spaceage polymers provide superior durability and lasting protection for your blacktop surface. **OMEGA A.F.S.** fills cracks up to 1/8" and seals worn surfaces. It restores beauty while protecting and preserving your valuable blacktop pavements. **OMEGA A.F.S.** offers the longest protective finish and is the best choice for your driveway, guaranteed.

PREPARATION: Driveways must be cleaned with **MEGA POWER**, spray on cleaner and degreaser before seal coating. For oil stains, apply **MEGA POWER** liberally and scrub into surface to penetrate oil spots. This step promotes proper bonding and will help prevent adhesion failures. Repair cracks and holes with **OMEGA P.D.S.** rubberized crack filler and patching products for long lasting results.

APPLICATION: Mix well. Apply with brush/squeegee applicator. If pavement gets hotter than 85°F, mist with water to cool surface so sealer doesn't dry too fast. However, do not allow water to puddle. Apply **OMEGA A.F.S.** in thin coats, as two thinner layers adhere better than one thick one. Do not apply to steeply sloped surfaces 20 degrees incline or more, as this may present a slip hazard. If slope is in question, test small area first, before applying to entire area. Note: Newly paved surfaces must cure at least 12 months before applying sealer.

COVERAGE RATE: Coverage rates vary depending upon the condition of the existing surface. A rush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away and sealed. Driveway must cure approx. 2-4 hours for foot traffic and 24-48 hours for vehicle traffic. Humid, or cloudy conditions may prolong curing time. Two thin coats are strongly recommended. Thick coats will result in uneven coverage, tracking and drying problems. Apply second coat perpendicular to the first after the first coat has cured approx. 3-6 hours. Approximate coverage for driveways in **GOOD CONDITION:** 400 SQ.FT./5 GAL. PAIL; **AVERAGE CONDITION;** 350 SQ. FT/5 GAL. PAIL.

CLEAN-UP: Soap and water when wet, or **NATURAL WAY** (diluted), a orange citrus cleaner when dry.

Health	1
Flammability	0
Reactivity	0
Protection	C

Areas of Use:

- *apartment complexes
- *hotels
- *amusement parks
- *cities and counties
- *dealerships
- *theatres
- *construction companies
- *grounds maintenance
- *school districts

Appearance and odor.....	N/A
Specific Gravity.....	N/A
% Volatile by Volume.....	0%
NFPA Fire Rating.....	Non-Flammable

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com

Fax: 707-864-8134