

Omega A.F.S.



Driveway filler and sealer

A.F.S. is a polymer fortified asphalt driveway coating designed for application over all blacktop surfaces in sound condition. This easy-to-stir, rubberized product will minimize the damaging effects of weather on asphalt driveways. **A.F.S.**'s heavy-bodied formulation fills and seals hairline cracks up to 1/8" wide. **A.F.S.** provides an attractive durable finish, and slip resistance on sloped surfaces. Asbestos free. Not for use on concrete.

Directions: Surfaces to be coated must be clean and free from dust, dirt, oil, grease, etc. Clean surface with Omega's **MEGA POWER** heavy duty degreaser and cleaner. (Citrus based cleaners should not be used on any asphalt surface). Stir before application. Apply to cool damp surface using a driveway brush. Spread evenly working coating into cracks. 1 gallon will cover approximately 100 square feet. Dries to touch in 4 hours, can be opened to traffic in 12 hours. **A.F.S.** has a 1 year shelf life.

Areas of Use:

- *apartment complexes
- *hotels
- *amusement parks
- *cities and counties
- *dealerships
- *theatres
- *construction companies
- *grounds maintenance
- *school districts



Health	0
Flammability	0
Reactivity	0
Protection	B

Appearance and odor.....	Black thick liquid, Mild odor
Specific Gravity.....	Concentrate - 1.0-1.2
VOC.....	55-75%
NFPA Fire Rating.....	Non-flammable

ONLY OMEGA™

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134