

Omega Asphalt Patch

Driveway patching compound



OMEGA ASPHALT PATCH is a ready-mixed compound that can be applied to holes and depressions in any solid base, such as asphalt, concrete, brick, stone or wood. It is ready to use and does not need any heating or mixing preparation. It is made from a combination of hard aggregate, asphalt, resins and wetting agents to match original blacktop surfaces. Tamped into place, it is ready for traffic at once. **OMEGA ASPHALT PATCH** can be applied to either wet or dry surfaces in any temperature from hot to sub-freezing. The particles in **OMEGA ASPHALT PATCH** are smaller than other patching compounds, therefore it will not re-crush under pressure and recreate the hole you have just filled. Provides a much more permanent repair than bagged products.

Directions: Spread **OMEGA ASPHALT PATCH** into area to be patched. Compress with hand tamper or roller. For larger areas, place board over patch and drive over to compact material into place. Areas exceeding one inch depth should be repaired in one inch increments. Use Omega's **NATURAL WAY** for effortless cleanup of tools, vehicles, and other surfaces contacted by asphalt patching compound.

Areas of Use:

- *cities and counties
- *school districts
- *colleges
- *apartment complexes
- *building maintenance
- *street departments

Health	1
Flammability	2
Reactivity	0
Protection	G

Appearance and odor.....	Black crushed stone, Oil odor
Specific Gravity.....	N/A
VOC/VOS.....	93 g/Liter
NFPA Fire Rating.....	Flammable

ONLY OMEGA™

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134