

# Omega P.D.S.



Pourable acrylic driveway  
crack sealer



**P.D.S.** is ideal for preventing moisture penetration and freeze/thaw surface attack. It is formulated for filling cracks 1/2" wide or smaller in any blacktop or concrete surface. Easy to use, no mixing or tools required. It dries to a black, durable, elastomeric seal. Excellent water resistance once dry. Use of Omega's **P.D.S.** provides a crack-free surface prior to applying Omega's **A.F.S.** driveway sealer. **P.D.S.** is ideal for maintenance staff that needs to make quick repairs with products that do not require training, yet do the job. Shelf life 1 year.

**Directions:** Cracks must be free of loose dirt and debris. Do not dilute. Shake container to mix before using. Pour into crack that has been lightly dampened but not wet. Fill until slightly above the surface edge. Wash tools with water unless product has dried, then use Omega's **NATURAL WAY** to remove.

#### Areas of Use:

- \*apartment complexes
- \*school districts
- \*cities and counties
- \*grounds maintenance
- \*amusement parks
- \*facilities maintenance departments
- \*dock areas/shipyards

Health	1
Flammability	0
Reactivity	0
Protection	G

Appearance and odor.....	Black liquid, Characteristic odor
Specific Gravity.....	Not Determined
VOC.....	20%
NFPA Fire Rating.....	Non-flammable

## ONLY OMEGA™

Fairfield, CA 94534  
1-800-571-7347 www.onlyomega.com Fax: 707-864-8134