

Omega Self Level Patch



Non-fibered liquid asphalt roof **ONLY OMEGA™**

coating and primer

OMEGA SELF-LEVEL PATCH is designed for the restoration and preservation of most types of flat roofing, including build-up, composition, smooth and granulated roll roofing. It does not need to be heated, so it is safe and easy to use and does not create offensive odors. **OMEGA SELF LEVEL PATCH** is also recommended as a primer to re-saturate and revitalize dried-out roofing felts, and can be used on cured concrete decks prior to application of **OMEGA ALL WEATHER PATCH** fibered asphalt roof coating. Provides a barrier against moisture and will not separate or settle. Use it to coat pipes, gutters, downspouts and other structural iron for protection against rust and water damage.

Directions: Area to be treated must be dry and free from dust, dirt and other foreign matter. Patch all cracks and seams with **OMEGA ALL WEATHER PATCH**. **OMEGA SELF LEVEL PATCH** can be applied with a brush, mop or spray equipment. On composition roofing use 1 gallon per 100 square feet. On concrete use 1 gallon per 150 square feet. Usage rates may vary depending on porosity of surface. Allow 4 hours to dry. Use Omega's **NATURAL WAY** for fast and easy cleanup.

Areas of Use:

- *cities and counties
- *school districts
- *high-rise buildings
- *hotels
- *prisons
- *building maintenance



Health	2
Flammability	2
Reactivity	0
Protection	C

Appearance and odor.....	Black liquid, Solvent Odor
Specific Gravity.....	Concentrate - 1.0
VOC.....	30-60%
NFPA Fire Rating.....	Flammable

ONLY OMEGA™

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134