

# Omega Total Last Seal



Fibered asphalt roof coating



**TOTAL LAST SEAL** is a heavy bodied asphalt coating used to re-saturate, preserve and protect composition, build-up, and smooth or granulated roofing. This coating can also be used on metal roofs and exterior foundation walls to provide a weatherproof seal. **TOTAL LAST SEAL** is easy to use, apply directly from container. Non-asbestos fibers help provide a thicker, more durable film. For temporary emergency repair on flat roofs while wet or raining, use Omega's **INSTA TEMP** temporary roof patch until the leak can be fixed properly. Coverage with **TOTAL LAST SEAL** is approximately 3 gallons per 100 square feet on built up roofs and masonry, and 1.5 gallons per 100 square feet on metal roofs. 2-3 days dry time before final cure.

**Directions:** Remove all dirt and debris, roof should be clean and dry before applying coating. Older, dried out roofing felts should be primed with Omega's **SELF LEVEL PATCH**. Repair all cracks, breaks and open seams with Omega's **ALL WEATHER PATCH** and allow to dry before coating. Apply a heavy coat with squeegee, roof brush, or mastic type spray gun.

#### Areas of Use:

- \*roofing/carpentry departments
- \*cities and counties
- \*school districts
- \*building maintenance
- \*apartment complexes
- \*shopping malls
- \*warehouses

Health	1
Flammability	2
Reactivity	0
Protection	G

Appearance and odor.....	Thick black tar-like substance
Specific Gravity.....	Not Determined
VOC.....	20%
NFPA Fire Rating.....	Flammable

## ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134