

Primal Primer

Primer Coating



Primal Primer coating for use on bare metal and bare wood surfaces. Provides massive rust protection. Fast drying sag free spray helps prevent rust and all chemical corrosion. Available in Light Gray and Red

Directions: **1.** Surface must be clean and dry before painting. For better adhesion, sand lightly with fine sandpaper or steel wool. **2.** Shake can at least one minute after rattle is heard and occasionally during use. For best results, use when can is between 70°F and 90°F (21°C and 32°C). **3.** Spray surface with steady even strokes at a distance of 8 to 10 inches. One light coat will provide the best finish. **4.** If clogging develops, turn nozzle 1/4 turn or remove and clean button slot. Do not stick objects into can opening. **5.** After painting, turn can upside down and spray for 2 seconds to clean nozzle. **6.** Discard empty can in trash pick up. Do not incinerate or compact.

Areas of Use:

- *any bare metal
- *bare wood surfaces
- *generators
- *maintenance equipment

Light Gray

Health	1
Flammability	4
Reactivity	3
Protection	-

Primal Primer Light Gray

Appearance and odor.....	Aromatic odor.
Specific Gravity.....	Concentrate - 0.77 - 0.85
VOC Content.....	567.7g/l/4.74 lb/gl
NFPA Fire Rating.....	Extremely Flammable

Red

Health	1
Flammability	3
Reactivity	3
Protection	G

Primal Primer Red

Appearance and odor.....	Color coating with solvent odor
Specific Gravity.....	Concentrate - 0.77 - 0.90
VOC by weight.....	52.7
NFPA Fire Rating.....	Extremely Flammable

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com/onlyomega Fax: 707-864-8134