

Super C

Industrial strength
sealant caulk



SUPER C is a highly adhesive, clear sealer that is designed to seal siding, trim, ducts, vents, gutters, roofing applications, windows, doors, restroom fixtures, and anywhere else that needs a waterproof seal. **SUPER C** remains flexible, weather-resistant, crack-free, and resists yellowing and UV rays. Tack free in 20 minutes and paintable after final cure in 24 hours (latex-based paint only). It will adhere to vinyl, aluminum, wood, glass, tile, metal, masonry, and drywall. For indoor or outdoor use, **SUPER C** can be applied even in below freezing temperatures. Service temperature range -35°F to 350°F.

Directions: Remove any old sealant and any loose dirt or debris. Trim nozzle to desired bead size, then puncture inner seal and load into caulking gun. Fill cracks and holes with sealant and clean up immediately with mineral spirits. For best results clean area with Omega's **MEGA POWER** degreaser to remove any grease or oily residue to ensure best adhesion. Do not apply when temperatures are below 20°, or when rain or freezing temperatures are eminent. Store away from extreme temperatures. Not recommended for under water applications. Joint size should not exceed 1/2". Allow to fully cure for 24 hours before exposure to water.

Areas of Use:

- *hotels
- *hospitals
- *apartment complexes
- *cities and counties
- *amusement parks
- *industrial facilities
- *plumbing departments
- *paint departments

Health	1
Flammability	2
Reactivity	1
Protection	B

Appearance and odor.....	Clear paste, Solvent Odor
Specific Gravity.....	Concentrate - 0.93
VOC.....	ND
NFPA Fire Rating.....	Flammable

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134