

Super Silicone Lubricant



Dry Silicone Spray USDA and FDA Approved. Rated H1



SUPER SILICONE LUBRICANT is specially formulated for use on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations which there is potential exposure of the lubricant to machinery used for producing, manufacturing, processing, preparing, packaging, transporting or holding food or food products. Heat stable from -450° to 450° F. **SUPER SILICONE LUBRICANT** lubricates all sliding surfaces and is excellent for sticking wood, metal, plastic, rubber or any other surface except those you may wish to paint later. Will not gum, run off or form messy residues. Great for use on sticky drawers, windows, door, hinges, locks, rollers, and zippers. Will prevent door locks from freezing. Waterproofs and protects leather, wood, chrome, canvas and rubber. USDA RATED: H1

Directions: Shake well. For best results area should be cleaned with Omega's **FEC** food grade cleaner prior to application. Hold can 6-8 inches from surface. Spray in short bursts until area is completely lubricated. Use just enough to lubricate, do not over spray.

Areas of Use:

- *hospitals
- *schools
- *conveyors
- *dishwashers
- *food processing equipment
- *hotels
- *banquet kitchens
- *hinges, locks, and handles

Health	1
Flammability	3
Reactivity	1
Protection	B

Appearance and odor.....	Clear liquid, Slight solvent odor
Specific Gravity.....	Concentrate - 0.77
Propellant.....	Mixture
% Volatile by Wt/By Vol. @ 77°F.....	9.5%
NFPA Fire Rating.....	Extremely-Flammable Spray

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com/onlyomega Fax: 707-864-8134