

T-Ease

Dry PTFE lubricant
and release agent



T-EASE is a non-chlorinated dry film lubricant and release agent made with an extremely fine Teflon fluorotelomer powder. Features outstanding microscopic film-forming properties and is heat stable from -100°F to +500°F. **T-EASE** is an odorless, stainless coating that is more slippery than silicone, graphite or oil, and is excellent for reducing low speed friction. Dry to the touch after application and evaporation. The dry film is non-oily and is not affected by most chemicals. When used as a release agent, allows parts to be painted without removing **T-EASE** from the surface. Safe on plastic, aluminum, rubber, glass, wood, paper, and metal.

Directions: For best results, make sure area is free of oil or grease residue by cleaning with Omega's **MEGA POWER** degreaser, and allowing to dry. Hold container 5-10 inches from surface and spray area with a thin film. Authorized by USDA.

Areas of Use:

- *hinges and drawer glides
- *rollers
- *conveyors
- *mower blades and undercarriage
- *window and closet door tracks
- *apartments
- *municipalities
- *bottling plants
- *maintenance departments
- *HVAC dampers

Health	2
Flammability	3
Reactivity	1
Protection	B

Appearance and odor.....	White liquid, solvent odor
Specific Gravity.....	Concentrate - 0.764
Propellant.....	Liquefied Petroleum Gas
VOC.....	~94%
NFPA Fire Rating.....	Extremely-Flammable Spray

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134